


FEATURES

- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current
- Low Inductance Package

APPLICATIONS

- Field Supply For DC Motors
- Line Rectifiers For Transistorized AC Motor Controllers
- Non-controllable Rectifiers For AC/DC Converter



MODULE TYPE

Module Type	V_{RRM} (Repetitive Peak Reverse Voltage)	V_{RSM} (Non-Repetitive Peak Reverse Voltage)	Unit
MMD250F120X	1200	1300	V
MMD250F140X	1400	1500	
MMD250F160X	1600	1700	
MMD250F180X	1800	1900	

ABSOLUTE MAXIMUM RATINGS

T_c=25°C unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
I_D	Output Current(D.C.)	Three phase, half wave, T _c = 90°C	250	A
I_{FSM}	Non-Repetitive Surge Forward Current	1/2 cycle, 50HZ, peak value T _c =45°C	2500	
		1/2 cycle, 60HZ, peak value T _c =45°C	2700	
I^2t	I^2t (For Fusing)	1/2 cycle, 50HZ, peak value T _c =45°C	31.2	KA ² s
		1/2 cycle, 60HZ, peak value T _c =45°C	30.2	KA ² s
P_D	Power Dissipation		1560	W
T_J	Junction Temperature		-40 to +150	°C
T_{STG}	Storage Temperature Range		-40 to +125	°C
V_{ISO}	Isolation Breakdown Voltage	AC, 50Hz(R.M.S), t=1minute	3000	V
Torque	Module-to-Sink	Recommended (M6)	3~5	N.m
Torque	Module Electrodes	Recommended (M6)	3~5	N.m
$R_{th (J-C)}$	Junction-to-Case Thermal Resistance	Per diode	0.45	K/W
		Per module	0.08	
Weight			250	g

MMD250F

ELECTRICAL AND THERMAL CHARACTERISTICS $T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Max.Reverse Leakage Current	$V_R = V_{RRM}$			500	μA
		$V_R = V_{RRM}, T_J = 125^\circ\text{C}$			10	mA
V_F	Forward Voltage	$I_F = 250\text{A}$			1.55	V
V_{T0}	For power-loss calculations only				0.85	V
r_T	$T_J = 125^\circ\text{C}$				2.7	m Ω




Figure1. Forward Voltage Drop vs Output Current




Figure2. Power dissipation vs. Output Current




Figure3. Max Non-Repetitive Forward Surge Current




Figure4. Output Current vs. Case temperature

