


## PRODUCT FEATURES

- Ultrafast Reverse Recovery Time
- Soft Reverse Recovery Characteristics
- Low Reverse Recovery Loss
- Electrically Isolated by DBC Ceramic
- High System Power Density
- Popular SOT-227 Package



## APPLICATIONS

- Inversion Welder
- Uninterruptible Power Supply (UPS)
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- Power Factor Correction (PFC) Circuit



## ABSOLUTE MAXIMUM RATINGS

$T_C=25^{\circ}\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
$V_R$	Maximum D.C. Reverse Voltage		1700	V
$V_{RRM}$	Maximum Repetitive Reverse Voltage		1700	V
$I_{F(AV)}$	Average Forward Current	$T_C=100^{\circ}\text{C}$	100	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=100^{\circ}\text{C}$	150	A
$I_{FSM}$	Non-Repetitive Surge Forward Current	$T_J=45^{\circ}\text{C}$ , $t=10\text{ms}$ , 50Hz, Sine	1100	A
		$T_J=45^{\circ}\text{C}$ , $t=8.3\text{ms}$ , 60Hz, Sine	1200	A
$I^2t$	$I^2t$ (For Fusing)	$T_J=45^{\circ}\text{C}$ , $t=10\text{ms}$ , 50Hz, Sine	6050	$\text{A}^2\text{s}$
		$T_J=45^{\circ}\text{C}$ , $t=8.3\text{ms}$ , 60Hz, Sine	7200	$\text{A}^2\text{s}$
$P_D$	Power Dissipation		625	W
$T_J$	Junction Temperature		-40 to +150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range		-40 to +125	$^{\circ}\text{C}$
$V_{isol}$	Insulation Test Voltage	AC, $t=1\text{min}$	3000	V
Torque	To-Sink	Recommended (M4)	0.7~1.1	N·m
Torque	To-Terminal	Recommended (M4)	0.7~1.1	N·m
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	0.20	$^{\circ}\text{C}/\text{W}$
Weight			26.5	g

## ELECTRICAL CHARACTERISTICS

 $T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{RM}$	Reverse Leakage Current	$V_R=1700\text{V}$	--	--	0.5	mA
		$V_R=1700\text{V}, T_J=125^\circ\text{C}$	--	--	10	mA
$V_F$	Forward Voltage	$I_F=100\text{A}$	--	--	2.37	V
		$I_F=100\text{A}, T_J=125^\circ\text{C}$	--	--	2.30	V
$t_{rr}$	Reverse Recovery Time	$V_R=1200\text{V}, I_F=100\text{A}$	--	140	--	ns
$I_{RRM}$	Max. Reverse Recovery Current	$di_F/dt=-1500\text{A}/\mu\text{s}, T_J=25^\circ\text{C}$	--	115	--	A
$t_{rr}$	Reverse Recovery Time	$V_R=1200\text{V}, I_F=100\text{A}$	--	330	--	ns
$I_{RRM}$	Max. Reverse Recovery Current	$di_F/dt=-1500\text{A}/\mu\text{s}, T_J=125^\circ\text{C}$	--	127	--	A

## FJ Package Outline (Dimensions in mm)

