


## PRODUCT FEATURES

- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current
- Low Inductance Package

## APPLICATIONS

- Field Supply For DC Motors
- Line Rectifiers For Transistorized AC Motor Controllers
- Non-controllable Rectifiers For AC/DC Converter
- UL:E332185



### Module Type

| Module Type | $V_{RRM}$<br>Repetitive Peak Reverse Voltage | $V_{RSM}$<br>Non-Repetitive Peak Reverse Voltage | Unit |
|-------------|--|--|------|
| MMD200F180X | 1800   | 1900   | V    |

### ABSOLUTE MAXIMUM RATINGS( $T_C=25^{\circ}C$ unless otherwise specified)

| Symbol     | Parameter/Test Conditions            |  | Values      | Unit              |     |
|------------|--------------------------------------|--|-------------|-------------------|-----|
| $I_D$      | Output Current(D.C.)                 | Three phase, full wave, $T_C=95^{\circ}C$      | 200         | A                 |     |
| $I_{FSM}$  | Non-Repetitive Surge Forward Current | 1/2 cycle, 50HZ, peak value, $T_J=45^{\circ}C$ | 2000        |                   |     |
|            |                                      | 1/2 cycle, 60HZ, peak value, $T_J=45^{\circ}C$ | 2200        |                   |     |
| $I^2t$     | For Fusing                           | 1/2 cycle, 50HZ, peak value, $T_J=45^{\circ}C$ | 20.0        | KA <sup>2</sup> S |     |
|            |                                      | 1/2 cycle, 60HZ, peak value, $T_J=45^{\circ}C$ | 20.1        |                   |     |
| $P_D$      | Power Dissipation                    |  | 1389        | W                 |     |
| $T_J$      | Junction Temperature                 |  | -40 to +150 | $^{\circ}C$       |     |
| $T_{STG}$  | Storage Temperature Range            |  | -40 to +125 | $^{\circ}C$       |     |
| $V_{ISO}$  | Isolation Breakdown Voltage          | AC, 50Hz(R.M.S), $t=1$ minute                  | 3000        | V                 |     |
| Torque     | Module to Sink                       | Recommended (M6)                               | 3~5         | Nm                |     |
| Torque     | Module Electrodes                    | Recommended (M6)                               | 3~5         | Nm                |     |
| $R_{thJC}$ | Junction to Case Thermal Resistance  |  | per diode   | 0.54              | K/W |
|            |                                      |  | per module  | 0.09              |     |
| Weight     |                                      |  | 250         | g                 |     |

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R. of China

Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: www.macmicst.com

# MMD200F180X

## ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol   | Parameter/Test Conditions                                   | Min.                                     | Typ. | Max. | Unit       |
|----------|---|--|------|------|------------|
| $I_{RM}$ | Maximum Reverse Leakage Current                             | $V_R = V_{RRM}$                          |      | 0.5  | mA         |
|          |   | $V_R = V_{RRM}, T_J = 125^\circ\text{C}$ |      | 10   |            |
| $V_F$    | Forward Voltage Drop  |  |      | 1.45 | V          |
| $V_{TO}$ | For power loss calculations only, $T_J = 125^\circ\text{C}$ |  |      | 0.85 | V          |
| $r_T$    |   |  |      | 3    | m $\Omega$ |




Figure 1. Forward Voltage Drop vs Forward Current




Figure 2. Power dissipation vs Output Current




Figure 3. Max Non-Repetitive Forward Surge Current




Figure 4. Output current vs Case temperature

